

## Microfil™ Junior

Absolute Rated Pleated Glass Fibre Cartridge Filters for Small-Scale Applications



A range of absolute rated cartridge filters are designed for retrofitting into existing junior-style housings. Featuring the latest developments in borosilicate glass fibre filter media technology, Microfil™ Junior cartridges are constructed from robust glass fibre and polypropylene filtration layers, offering removal ratings from 0.5 to 5 micron absolute.

Microfil™ Junior cartridges are suitable for absolute removal of unwanted particulates and for pre-filtration to membrane filters. Microfil™ Junior cartridges incorporate a polypropylene pre-filtration layer, combined with a high dirt capacity glass fibre media, resulting in longer service life, improved operating costs and smaller process footprint. The Microfil™ Junior filter cartridges are highly resistant to integrity failure caused by steam sterilisation and have excellent chemical compatibility characteristics.

They are suitable for applications ranging from bioburden reduction to the clarification of a wide range of process liquids and end products. Available in J-style with internal O-ring, S-style with moulded flange seal and L-style with 4-lug locking end cap with double external O-rings.

### Typical Applications

- Small-scale pharmaceuticals and bio-processing
- Pilot-scale studies
- Batch processing

### Ordering Information

Product Code: 1 M 2 3 4

1: Configuration		2: Pore Rating		3: Length		4: Seals (J/L Style)	
J	J-Style	P5	0.5µm	25	77.5mm (2.5")	A	Ethylene Propylene
S	S-Style	P8	0.8µm	50	136mm (5")	B	Silicone
L	L-Style	01	1µm			C	Viton®
		02	2µm			D	Nitrile
		05	5µm			E	FEP Encap. Viton®
						G	FEP Encap. Silicone

## Features and Benefits

- Zeta potential
- High filtration area
- Guaranteed removal ratings
- Suitable for steam and hot water sanitisation
- Full traceability
- Controlled manufacturing environment

## Specifications

### Materials of Manufacture

Filter media:	Glass fibre
Pre-filtration layer:	Polypropylene
Support layers:	Polypropylene
Inner core:	Polypropylene
Outer support:	Polypropylene
End fittings:	Polypropylene
Support ring:	Stainless steel

### Cartridge Dimensions (Nominal)

Effective Filtration Area:	0.15m <sup>2</sup> (1.6ft <sup>2</sup> ) per 5" length.
Diameter:	56mm (2.2")
Length:	77.5mm (2.5") 136mm (5")

### Cartridge Treatment

Standard:	Cleaned without further treatment
Flushed:	Flushed with pyrogen-free water

### Gaskets and O-Rings

J-style:	Silicone (other materials are available on request)
S-style:	Not supplied
L-style:	Silicone (other materials are available on request)

### Maximum Differential Pressure

Normal flow direction at:	
20°C (68°F):	6.0 bar (87psi)
80°C (176°F):	4.0 bar (58psi)
100°C (212°F):	3.0 bar (44psi)
120°C (248°F):	2.0 bar (29psi)
Reverse flow direction at:	
20°C (68°F):	2.1 bar (30psi)
80°C (176°F):	1.0 bar (15psi)
100°C (212°F):	0.5 bar (7psi)

### Operating Temperature

Maximum continuous: 80°C (176°F)

### Sterilisation

J-style:	<i>In situ</i> steam 70 x 25 minute cycles at 130°C (266°F)
S-style:	Autoclave 100 x 25 minute cycles at 125°C (257°F)
L-style:	<i>In situ</i> steam 70 x 25 minute cycles at 130°C (266°F)

### Extractables

Minimum total extractables. Please refer to the Microfil™ Validation Guide.

### Integrity Testing

Microfil™ Junior filter cartridges are batch tested for integrity using the Bubble Point Test. Please contact us for procedural details.

### Clean Water Flow Rates

- Typical clean water flow rate:  
A 136mm (5") Microfil™ Junior cartridge exhibits the flow- $\Delta$ P characteristics indicated below, for solutions with a viscosity of 1 centipoise.
- Other solutions:  
For solutions with a viscosity of greater than 1 centipoise, multiply the indicated differential pressure by the viscosity in centipoise.

