

Microcap™ GPVDF

Hydrophilic PVDF
Membrane Capsule Filters



Microcap™ GPVDF capsule filters consist of a single layer, hydrophilic, high capacity polyvinylidene fluoride (PVDF) membrane. These filters are used for bioburden control and clarification/pretreatment in aqueous liquids.

Pore sizes range from 0.22 to 1.0 µm and the filter devices scale from laboratory to full production using identical materials to ensure consistent results.

The hydrophilic GPVDF capsules deliver high flow and throughput with the broad chemical compatibility of a fluoropolymer, making them ideal for filtering aggressive aqueous solutions.

Typical Applications

Bioburden control in:

- SVPs and LVPs
- Buffers
- Plasma products
- WFI
- Serum
- Vaccines
- CIP solutions

Features and Benefits

- Excellent flow rates with high throughput.
- Excellent chemical compatibility.
- Non-fibre releasing.
- USP Class VI approved.
- Uses FDA compliant materials.

Ordering Information

Product Code: 7018-6

XXX - X - XX - X - X

Micron Rating (µm)		Pre-sterilised		Length (in)		Inlet		Outlet	
P22	0.22	N	Non-sterile	02	2	A	1/4" Female NPT	A	1/4" Female NPT
P45	0.45	S	Sterile	05	5	B	1/4" Male NPT	B	1/4" Male NPT
P65	0.65			10	10	C	3/8" Female NPT	C	3/8" Female NPT
P80	0.80			20	20	D	1/2" Female NPT	D	1/2" Female NPT
001	1.0			30	30	E	1/2" Male NPT	E	1/2" Male NPT
						F	1" - 1 1/2" Sanitary	F	1" - 1 1/2" Sanitary
						G	Hose Barb*	G	Hose Barb*

*Fits hoses/tubes with inner diameter 11/32 to 9/16 inches

Specifications

Materials of Manufacture

Housing:	Polypropylene
Filtration media:	Hydrophilic High Capacity Polyvinylidene Fluoride (PVDF) Membrane
Media support:	Polypropylene
End caps:	Polypropylene
Centre core:	Polypropylene
Outer support cage:	Polypropylene
Sealing method:	Thermal bonding

Sanitisation/Sterilisation

Autoclave:

121°C (250°F), 30 min, 5+ cycles

Chemical sanitisation: Performed using industry standard concentrations of hydrogen peroxide, peracetic acid, sodium hypochlorite and other selected chemicals.

Pre-sterilised:

Hydrophilic PVDF capsules are offered in both non- and pre-sterilised forms.

Note:

GPVDF capsules are not designed for steam-in-place (SIP).

Filtration Area

Capsule length				
2"	5"	10"	20"	30"
1.0ft ² (0.09m ²)	2.8ft ² (0.26m ²)	6.0ft ² (0.56m ²)	12.0ft ² (1.11m ²)	18.0ft ² (1.67m ²)

Maximum Operating Parameters

Liquid Operational Pressure	5.52 bar at 20°C (80 psi at 68°F)
Gases Operational Pressure	4.14 bar at 20°C (60 psi at 68°F)
Operating Temperature (water)	43°C at 2.07 bard (30 psid at 110°F)
Reverse Differential Pressure	3.45 bard at 20°C (50 psid at 68°F)
Recommended Changeout Pressure	2.41 bard (35 psid)

Clean Water Flow Rates

A 2" capsule with 1" sanitary inlet and outlet point, exhibits the flow-ΔP characteristics indicate below, for solutions with a viscosity of 1 centipoise.

