

Sinterflo® M

Pleated Metal Mesh Filter Cartridges

Porvair Filtration Group manufacture a range of industry standard stainless steel filter cartridges suitable for use in a wide range of industries, including petrochemical.

The robustness of design, that is provided by a fully welded metallic element or cartridge, is required to resist deterioration in harsh operating environments where the fluids present are aggressive, high temperatures are experienced or where the operating differential pressures are high.

For some filtration applications, the use of a conventional disposable polymeric cartridge may simply be environmentally unacceptable and the use of a re-cleanable cartridge will often give more cost effective filtration.

These filter cartridges are offered in the following media configurations:

- Sinterflo® F Sintered Metal Fibre
- Sinterflo® P Sintered Metal Powder
- Sinterflo® M Metal Mesh
- Sinterflo® MC Sintered Metal Composite

Sinterflo® M precision woven meshes are manufactured in various types of weaves. Plain square weave is available for simple sieving duties through various weave patterns (reverse plain dutch, broad mesh twill and single plain weave). Dutch twill weave is provided for the most comprehensive selection of surface filtration duties.

Sinterflo® M demonstrates good permeability, high tensile strength and is available from single wrap designs through to complex multi-layered structures in pleated constructions to optimise the area available. These meshes can be manufactured in diffusion bonded versions to increase performance security of pore shape and size and have the broadest range of pore sizes of any filter media type.


Sinterflo® M is available in 316L stainless steel as standard with other alloys such as 304L stainless steel, Inconel®, Hastelloy® and Monel® on request.



Applications

Typical applications for our Sinterflo® M cartridges include the following:

- **Catalyst recovery and retention**
For use in the collection of catalyst dust on various catalyst hoppers or FCC regenerator stream on refineries.
- **Gasification and chemical production**
For the clean-up of syngas from pet coke/coal feedstock and for IGCC trains, amongst others, for the production of hydrogen and other chemicals.
- **Vent filters**
For emission control of dust in various industry applications.
- **Agrochemical**
Typically for ammonia systems used on nitric acid and urea plants.
- **Steam**
For applications in the chemical, food, beverage and pharmaceutical industries.
- **Pharmaceutical powder recovery**
For medium pressure applications in dryers and blenders.
- **Polymer melt**
For the filtration of hot polymers used for the manufacture of man-made polymer films, fibres and bottles.



Cross section of
Sinterflo® M Metal Mesh

Magnification of
Sinterflo® M Metal Mesh

Features and Benefits

- Sinterflo® M cartridges**
 Sinterflo® M Metal mesh is a robust, non-shedding media which provides resistance to mechanical abrasion.
- Manufactured in various types of weaves**
 Available in plain square mesh, reverse plain dutch, broad mesh twill, single plain weave and dutch (Hollander) twill weave to give the most defined absolute rating.
- Precise aperture**
 Our cartridges are manufactured to precise aperture requirements of both size and shape.
- Good permeability**
 Our cartridges have an open structure which provides good permeability.
- All-welded, robust construction**
 The all-welded construction eliminates the need for resin bonded end caps. Its robust structure ensures long service life and its suitability to the most demanding of environments.
- Single layered designs to complex multi-layered structures**
 These can be manufactured in a variety of layer combinations depending on the specific grade and micron requirement.
- Pleatable structure, offering higher filtration area per cartridge**
 The pleated structure enables the reduction of the number of cartridges and overall footprint of the installation.
- Smooth surface variant**
 The manufacturing process of our cartridges enables us to achieve a smooth surface variant. This is the preferred choice for backwash applications.

- Other alloys available**

Available in 316L stainless steel as standard with other alloys such as 304L stainless steel, Inconel®, Hastelloy® and Monel® on request.

Cartridge Construction


The Sinterflo® range of filter cartridges and elements are constructed in stainless steel 316L as standard. These filters are available in a pleated cartridge configuration, giving 0.13m² (1.40ft²) of active filtration area per 10" length.

This pleated cartridge design uses a precision pleated pack, comprising of protection and support meshes either side of the filter medium, around a support core to provide nearly three times the effective filtration area of the cylindrical element.


The filter media and support meshes are either plasma or TiG seam welded and the media support core and end fittings are fully TiG welded together. This method of construction guarantees cartridge integrity, eliminating the risk of bypassing and the presence of extractables derived from bonding agents.

The method of construction and materials used allow for operation from -269°C (-452°F) to 1000°C (1832°F) and up to 25bar (363psi) differential pressure in normal flow direction. Higher operating temperatures and differential pressures can be accommodated by design.


In the double open ended configuration, in addition to the support core, there is a 25mm (1") inner core to assist the location of multiple length units onto tie rods. Our pleated cartridges are supplied with a guard as standard for backflow/backflushing protection up to 3bar (44psi) differential.




226 End Fitting




222 End Fitting



Double Open Ended Fitting



Threaded End Fitting



Specifications

Materials of Manufacture

316L stainless steel standard. 304L stainless steel, Inconel®, Hastelloy® and Monel® on request or by process selection. Additional alloys are available on request.

Cartridge Dimensions*

Diameter: 66mm (2.6") as standard.
 Lengths: 125mm (5"), 250mm (10"), 498mm (20"), 745mm (30") and 1012mm (40").

*Other diameters and lengths available on request.

Effective Filtration Area

0.13m² (1.40ft²) per 250mm (10") cartridge.

Gaskets and O-Rings*

EPDM as standard. Nitrile, PTFE, Silicone, Viton® and PTFE coated Viton® available on request or by process selection.

* FDA approved seals are available.

Typical Maximum Differential Pressure* (all lengths)

Normal flow direction: 25bar (363psi)

Reverse flow direction: 3bar (44psi)

* Grade dependant.

Operating Temperature


Maximum continuous: From -195°C (-319°F) to 340°C (644°F) seal limiting,
 From -269°C (-452°F) to 1000°C (1832°F) alloy limiting.

Sinterflo® M Stainless Steel Media Grades


Micron Rating (µm) (micron code)	Liquids (µm)* (99.9% efficiency)	Gases (µm) (99.9% efficiency)
3 (0003)	10	2
5 (0005)	18	13
10 (0010)	25	18
15 (0015)	35	25
25 (0025)	30	20
30 (0030)	40	30
35 (0035)	50	45
70 (0070)	75	60

* Hard spherical particle maximum passed.


Typical Flow Rates in Water*



Typical Flow Rates in Air*



Typical Flow Rates in Steam*



* Using a 10 inch cartridge, at ambient temperature.

Additional Information

Range

Suitable for use in **Porvair** filter housings and as direct replacements for existing cartridges, Sinterflo® M cartridges can be supplied with end fittings to suit most hardware installations without modification. They are available in single or multiple module units in lengths of 10, 20, 30 and 40 inches, and a standard outside diameter of 2.6 inches (66mm). Each cartridge is supplied with all necessary seals or O-rings to ensure chemical compatibility.

Quality Assurance

Quality is at the heart of every stage of our operation and a fundamental part of our culture. We are ISO9001 approved at all of our manufacturing facilities and hold many other accreditations for the various industries we serve.

Product Innovation, Manufacturing and Testing

We understand that product development involves building multidiscipline teams, not only within the company, but often in partnership with our customers, improving project efficiency and ensuring complete customer satisfaction. This continuous development of products and materials is vital, to enable us to offer new and better solutions to applications. **Porvair** has implemented various methodologies to drive out waste and process variance across the company to achieve the ultimate goal of zero defects.

We have a dedicated team of scientists, engineers, production and quality professionals working towards the best possible filtration solutions for our customers. We have a fully equipped test house and laboratory, and our experienced design engineers use the latest AutoCAD® technology, with 3D solid modelling, integrated with a finite cartridge analysis system to give full structural assurance capability.

Filter Housings

Please contact a **Porvair Filtration Group** representative for further information on our range of filter housings.

porvair
filtration group

Porvair Filtration Group Ltd.

Queensway
Stem Lane, New Milton,
Hampshire, BH25 5NN, UK
Tel: +44 (0)1425 612010
Email: info@porvairfiltration.com

Porvair Filtration Group Inc.

301 Business Lane
Ashland, Virginia 23005, USA
Tel: +1 804 550 1600
Email: infoUS@porvairfiltration.com

Porvair Filtration Group

Chengdong Area
Square Industrial Park, North District
Xiaonan Economic Development Zone
Xiaogan, 432000, China
Tel: +86 (0)712 2878955
Email: infoCN@porvairfiltration.com

www.porvairfiltration.com

Porvair Filtration India PVT. Ltd.

Gangotri Glacier Annex, Kavesar
Opposite Vijay Nagari, Off Ghodbunder Road
Thane (W), 400607, India
Tel: +91 22 25 976464 / +91 22 25 976465
Email: infoIN@porvairfiltration.com

Porvair and Sinterflo are registered trademarks of Porvair plc.

AutoCAD is a registered trademark of Autodesk Inc.

Hastelloy is a registered trademark of Haynes International Inc.

Inconel and Monel are registered trademarks of Special Metals Corporation.

Viton is a registered trademark of DuPont Performance Elastomers LLC.

© Copyright 2014, Porvair Filtration Group Ltd. All rights reserved.

Whilst every effort has been made to ensure the accuracy of this document, due to continuous product development, the data contained is subject to constant revision and Porvair Filtration Group Ltd. reserves the right to change, alter or modify its contents.